

EXPLOSION HAZARDS

1250 Terminal Tower, Cleveland, OH 44113 216/621-6425 Plants: Cleveland, OH; Livonia, MI; Tucker, GA; Downey, CA Canada: Armalite; Toronto and Montreal



MAY 2 8 1982

Product Name:	CEE-BEE	A-95 2	DPM	968 MAY 2	·		
CHEMICAL NAME	ompound			EMERGENCY PHONE NO. 213/861-1211			
SYNONYMS	fide polymer remover				DATE FORM ISSUED July 1979		
FORMULA		blend					,
		I. H	IAZARDO	US INGREDIENTS			
MATERIAL		TLV (UNITS) %		MATERIAL		TLV (UNITS)	%
*Methylene chloride		(California) 200 ppm	70-90	*Methylene chloride		(EPA) 500 ppm	
Methanol		200 ppm	5-10				
Thioglycolic acid		not listed	< 5			·	
_		-					
			II. PHYS	SICAL DATA	•		
BOILING POINT 760 mm Hg	104	-		FREEZING POINT	n/a		
SPECIFIC GRAVITY (H ₂ O = 1)	1.220			VAPOR PRESSURE AT 20° C, mm Hg	280		
VAPOR DENSITY (AIR = 1)	2.90			SOLUBILITY IN WATER	insoluble		
PERCENT VOLATILES BY VOLUME	97	·		EVAPORATION RATE (butyl acetate)	14		
APPEARANCE	clear, go	lden brown l	iquid	ODOR	predominately sulfide		
		III. FIRE	AND EXPL	OSION HAZARD DATA			
FLASH POINT MEST METHOD)		point up to nitial boil.		FLAMMABLE LIMITS	Upper	n/a	
AUTOIGNITION TEMPERATURE	n/	a		(% BY VOLUME)	Lower	n/a	
EXTINGUISHING MEDIA	n/a						
SPECIAL FIREFIGHTING PROCEDURES	n/a						
UNUSUAL FIRE AND		n/a					

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations.

applicable laws and regulations.
THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGMENT FORM.

	IV. HEALTH HAZARD DATA						
THRESHOLD LIMIT VALUE	200 ppm						
EFFECTS OF OVEREXPOSURE	Irritates eyes and skin						
EMERGENCY AND FIRST AID PROCEDURES	For eyes & skin, flush with water for at least 15 minutes. If eye irritation persists, seek medical attention. Harmful if swallowed - for ingestion, do NOT induce vomiting - seek medical attention.						
	V. REACTIVITY DATA						
STABILITY	CONDITIONS TO AVOID						
Unstable _X_Stable							
IMCOMPATIBILITY (Materials To Avoid)	n/a						
Hazardous Decomposition Products	phosgene may be formed when exposed to flames						
Hazardous Polymerization May X Will Not Occur Occur	CONDITIONS TO AVOID						
	VI. SPILL OR LEAK PROCEDURES MALE						
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	Absorb on clay and dispose of in landfill.						
WASTE DISPOSAL METHOD	Allow solvent to evaporate and burn residue Comply with all Federal, State & Local Environmental Regulations.						
	VII. SPECIAL PROTECTION INFORMATION						
RESPIRATORY PROTECTION	required in areas of high vapor concentration NIOSH Certified Equipment List (See Pub.80-144)						
VENTILATIONS	LOCAL EXHAUST SPECIAL						
VENHERMONS	MECHANICAL X OTHER						
PROTECTIVE GLOVES	Solvent resistant EYE PROTECTION Goggles or face shield EQUIPMENT protective clot						
	VIII. SPECIAL PRECAUTIONS						
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	store in cool, dry place						
OTHER PRECAUTIONS	Wash thoroughly after handling. Loosen bung slowly when removing to relieve internal pressure						

9520 EAST CEE BEE DRIVE • DOWNEY, CALIFORNIA 90241 • TELEPHONE (213)

361-1211

Corporate Headquarters: McGean Chemical Company, Inc. • 1250 Terminal Tower • Cleveland, Ohio 44113 • Telephone (216) 621-6425 • Telex 98-0403

CEE-BEE A-95

GENERAL DESCRIPTION

Used to dissolve uncured and cured polysulfide polymers, such as Thiokol sealants and adhesives.

ADVANTAGES

- 1. Effectively removes uncured polysulfide polymers from sealant guns, brushes spatulas and other tools and equipment.
- Removes most cured polysulfide polymers by bond-release action.
- 3. Unlike many sealant removers, it can be covered with a water seal to reduce evaporation losses.
- 4. If evaporation loss is reduced to a minimum by maintenance of an adequate water seal, working life will be limited only by excessive quantity of sealant dissolved in solvent layer.
- Safe for use on most metals, including aluminum and steel.
- 6. Non-flammable no flash point up to and including initial boiling point.

INTENDED USE

- 1. Removal of uncured polysulfide polymers.
- OPERATION:

Use as received with or without a water seal (approximately 20% of total volume). Immerse parts until coating is removed from parts. Remove from tank and rinse thoroughly with toluene or other volatile solvent to remove any residues. Wipe dry with clean cloths or allow to air dry.

- 2. Removal of cured polysulfide polymers.
- OPERATION:

Use as received with or without a water seal (approximately 20% of total volume). Immerse parts until coating is sufficiently loosened from surface. Some agitation may be required. Remove from tank and rinse thoroughly with toluene or other volatile solvent to remove any residues. Wipe dry with clean cloths or allow to air dry.

PROPERTIES

Clear liquid containing chlorinated hydrocarbons. Slightly acidic Non-flammable.

PRECAUTIONS

Caution - contains chlorinated hydrocarbons. Avoid eye and skin contact. Use with adequate ventilation. Avoid breathing vapors. Use respirator in areas of high vapor concentration.

DO NOT TAKE INTERNALLY

In case of accidental contact with eyes, flush with water for at least 15 minutes. If irritation persists, seek medical attention. For skin contact, flush with water for at least 15 minutes. For ingestion, induce vomiting - keep warm and quiet and obtain medical attention. Never give anything by mouth to an unconscious person.

Store in cool, dry area.

revised 779/bg